



GAFGLAS®

#75 Base Sheet

Description

GAFGLAS#75 Base Sheet is a premium roofing base sheet constructed with a strong glass mat that is coated on both sides to assure a closed-sheet design to prevent asphalt bleed-through. The sealed sheet also serves as an effective flame retarder for the application of torch-applied modified bitumen membranes.

Uses

GAFGLAS#75 Base Sheet is engineered for use in the construction of GAFGLAS built-up and RUBEROID® modified bitumen roofs. It is suitable for nailable specifications, such as plywood, where bleed-through is a concern.

Advantages

- Extra strength for excellent nail-holding ability. Superb tensile strength and resilience and no bleed through, thereby reducing risks of splitting and cracking of membrane.
- Will not rot, curl, or shrink; dimensionally stable for improved membrane performance.
- Designed to meet UL Class A ratings.
- Rolls out flat for easy installation.

Applicable Standards

- UL approved for use in the construction of Class A, B, or C roofs (Type G2 BUR)
- FM Approved
- ASTM D-4601, Type II
- Dade County Product approval

Product Data (Approximate)

Roll Size.....39.4" x 97.5'
(1.0m x 29.7m)
Coverage Per Roll.....3 squares
Roll Weight.....75lbs.(34.1 kg)

