

# GAFGLAS® **EnergyCAP**™

**BUR Mineral Surfaced Cap Sheet**



## Description

GAFGLAS® EnergyCap™ BUR is a mineral surfaced cap sheet surfaced with extra fine mineral granules and a factory applied layer of TOPCOAT® EnergyCote™ elastomeric coating.

## Uses

GAFGLAS® EnergyCap™ BUR mineral surfaced cap sheet is used as the surfacing ply in the application of hot applied built-up roofs and as a top ply in base flashing construction.

## Advantages

- Cost effective—ENERGY STAR® qualified, Title 24 compliant cap sheet, without the added expense of installing a reflective coating after the roof is installed.
- Guarantees up to 20 years available.
- Durability—glass base resists the effects of moisture on the roof system.
- Code approvals—UL Class A, B, or C membrane constructions are available.

## Applicable Standards

- UL Approved for use in the construction of Class A, B, or C roofs
- ASTM D 3909, ASTM E903, ASTM E408
- ICC Evaluation Report Pending
- Title 24 compliant, ENERGY STAR® qualified

## Product Data (Approximate)

Roll Size.....1 sq. (106.9 ft<sup>2</sup> or 9.9m<sup>2</sup>)  
 Roll Length.....32.6' (9.9m)  
 Roll Width.....39.4" (1.0m)  
 Weight.....73 lbs. (33.1 kg)

## Reflectivity and Emittance

Reflectivity.....80%  
 Emittance.....0.90

